



Main

Range of product	Rapstrap
Product or component type	Releasable cable tie
Mounting mode	Clamped

Complementary

Maximum load	<= 10 kg
Bundle size	< 5 mm > 80 mm
Material	Polyurethane elastomer
User manual language	Danish Finnish Norwegian Swedish
Thickness	1.25 mm
Length	300 mm
Width	10 mm
Quantity per set	Set of 24
Colour	Black
Type of packing	Plastic bag with eurohole

Environment

Ambient air temperature for operation	Brittle point at -68 °C No-load at -20...60 °C
Flame retardance	HB conforming to UL 94
Environmental characteristic	Limited resistance to prolonged UV exposure

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 4Q2016

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.